

防爆蜂鳴器+閃爍警示燈 eXL07



- ▶適用危險場所 Zone 1
- ▶II 2 G Ex de IIB T3
- ▶本體材質:GRP
- ▶音量 approx.: 116 dB(A)
- ▶電壓: 24VDC 或 230 VAC
- ▶保護等級: IP66

防爆閃爍警示燈



- ▶適用氣體,粉塵危險場所 Zone 2 + 21
- ▶II 2 G Ex emb [ib] IIC T4 Gb
- ▶II 2 D Ex mbD A21 Db
- ▶燈罩材質:耐撞擊 PC
- ▶5 種 LED 光源顏色:  
白,紅,黃,綠,藍
- ▶4 種模式:常亮-閃光-閃爍-旋轉
- ▶電壓: 24VDC 或 230 VAC
- ▶保護等級: IP66

防爆 LED 警示燈 dSLB 20 LED



- ▶適用氣體,粉塵危險場所 Zone 1 + 21
- ▶II 2G Ex de IIC T6 Gb
- ▶II 2D Ex tb IIIC T95 °C, T80 °C Db
- ▶本體材質:防海水耐腐蝕鋁合金
- ▶5 種 LED 光源顏色:  
白,紅,黃,綠,藍
- ▶4 種模式:常亮-閃光-閃爍-旋轉
- ▶電壓: 24VDC 或 80-265 VAC
- ▶保護等級: IP66

防爆蜂鳴器 dEV20



- ▶適用氣體,粉塵危險場所 Zone 1 + 21
- ▶II 2G Ex d e IIB+H2 T6 Gb
- ▶II 2 D Ex tb IIIC T85 °C Db
- ▶本體材質:防海水耐腐蝕鋁合金
- ▶音量 approx.: 115 dB(A)
- ▶保護等級: IP66

防爆警報器 mHP11



- ▶適用危險場所 Zone 1 + 2
- ▶II 2 G Ex emb II T5
- ▶本體材質:Polycarbonate
- ▶音量 approx.: 108 dB(A)
- ▶保護等級: IP54

防爆蜂鳴器 DB3B



- ▶適用氣體,粉塵危險場所 Zone 1 + 21
- ▶Ex d IIC T4
- ▶Ex tb IIIC T135 °C
- ▶電壓: 12-48 VDC / 110-254VAC
- ▶本體材質:GRP
- ▶不鏽鋼 SS316 金屬配件
- ▶音量: Up to 125 dB
- ▶保護等級: IP66

防爆喇叭 DB16 25W/30W



- ▶適用氣體,粉塵危險場所 Zone 1 + 21
- ▶Ex de IIC T3 Gb
- ▶Ex tb IIIC T110 °C Db
- ▶音頻電壓: 100V or 8Ω
- ▶瓦數: 可選擇 25W 或 30W
- ▶本體材質:GRP
- ▶音量: Up to 122 dB/30W
- ▶Up to 121 dB/25W
- ▶保護等級: IP66

火災警報器 PH1



- ▶適用氣體,粉塵危險場所 Zone 1 + 21
- ▶Ex d IIC T6 Gb
- ▶Ex tb IIC T85 °C Db
- ▶本體材質:GRP
- ▶不鏽鋼 SS316 金屬配件
- ▶保護等級: IP66

不鏽鋼接線盒 SM87JB



- ▶適用危險場所 Zone 1 + 2
- ▶Ex II 2GD, Ex d IIC T4/5/6 Gb
- ▶Ex tb IIIC T135/100/85 °C Db
- ▶本體材質:不鏽鋼 SS316
- ▶附端子 440V, 25A x 12 pcs
- ▶尺寸: 122 Ø x 87.5(高)mm
- ▶保護等級: IP66