

DC 直流控制器系列

DC controller			
Type designation	Supply voltage range (V _{DC})	Designed for:	Page
UPC3-24	18 - 35	PSR312/PSR327 racks: DCR PSR327-XX	16
UPC3-48/60	35 - 75		
UPC3-110	80 - 135		
UPC3-220	185 - 275		
UPC3-24S	19.2 - 35	PSR308 racks: DCR PSR308-XX PSC305 racks: DDR PSC305-XX	15/18
UPC3-48/60S	35 - 75		
UPC3-110S	80 - 135		
UPC3-220S	185 - 275		
Smartpack Extended	24	Flatpack2- and Powerpack-based DC power solutions	45
Smartpack WEB/SNMP			

控制裝置 **UPC3** 可用於對電源系統進行一般監控。

擴展模塊

Type	Connector	Mounting	DC Controller compatibility
DCC-RDD	CAN-Bus	Door	UPC3, UPC3S
DCC-RDP	CAN-Bus	Door	UPC3, UPC3S
DCC-RB6	CAN-Bus	DIN-rail	UPC3, UPC3S
DCC-DI8	CAN-Bus	DIN-rail	UPC3, UPC3S
DCC-CN1	CAN-Bus, Ribbon cable	DIN-rail	UPC3, UPC3S



敦川企業有限公司

Tel: (02)2729-7727 • Fax: (02)2729-1127

Email: sunlux@ms14.hinet.net